



**HEIN | LEHMANN**

**CONIDUR®**

**OPEN AREA FOR CONIDUR® FINE HOLE  
SHEETS**

# OPEN AREA FOR CONIDUR® FINE HOLE SHEETS

## STANDARD VALUES FOR MILLS AND CENTRIFUGALS

Perforation	Max. open area (A0) %						
	Initial sheet thickness						
	0.35	0.50	0.70	1.00	1.25	1.50	2.00
0.06	2.0						
0.10	3.5	2.9					
0.15	5.5	4.3	2.5				
0.20	7.0	5.5	3.7	3.0			
0.25	8.5	7.0	5.0	4.0			
0.30	10.0	8.3	6.4	4.8	3.7		
0.35	11.3	9.5	7.3	5.6	4.2	3.1	
0.40		10.6	8.5	6.5	4.9	3.8	3.0
0.50		12.5	10.4	8.0	5.9	4.9	4.0
0.60		14.0	12.3	9.2	7.0	6.0	5.0
0.70		15.0	14.0	10.5	8.0	7.3	6.2
0.80			15.5	11.6	9.0	8.5	7.1
0.90				12.7	10.0	9.6	8.2
1.00				13.8	10.8	10.5	9.4
1.25				15.3	12.9	13.0	11.2
1.50					15.0	14.8	13.0
1.75						16.0	15.0
2.00						17.1	16.9
2.50							20.4
3.00							24.0
3.50							27.0
4.00							29.0
4.50							33.2
5.00							16.2
5.50							17.0
6.00							19.7
6.50							22.3

The maximum open area A0 [%] results from the smallest dimensions for pitch and feed and depends on the material.