



HEIN | LEHMANN

CONIDUR®

**OPEN AREA FOR CONIDUR® SLOTTED
HOLE SHEETS**

OPEN AREA FOR CONIDUR® SLOTTED HOLE SHEETS

STANDARD VALUES FOR MILLS AND CENTRIFUGALS

Perforation	Max. open area (A0) %					
	Initial sheet thickness					
	0.20	0.25	0.35	0.50	0.70	1.00
0.05 x 1	5.5	5.2				
0.06 x 2	5.1	4.8	4.5			
0.10 x 2			7.0	6.0		
0.15 x 2			9.0	8.0		
0.25 x 2			12.5	11.0		
0.30 x 2			13.0	12.0		
0.10 x 3			9.0	7.0		
0.15 x 3			11.0	9.0	6.0	
0.20 x 3			14.0	11.0	8.0	
0.25 x 3			15.0	13.0	9.5	
0.30 x 3			17.0	14.0	11.0	
0.40 x 3			19.5	17.0	14.0	
0.50 x 3			21.0	20.0	16.0	
0.15 x 4			11.0	9.0	6.0	
0.20 x 4			14.0	11.0	8.0	
0.25 x 4				13.0	9.5	9.0
0.30 x 4				14.0	11.0	10.5
0.40 x 4				17.0	14.0	13.5
0.50 x 4				20.0	16.0	15.0
0.60 x 4				23.0	18.0	17.0
0.70 x 4				26.0	20.0	19.0
0.80 x 4				27.0	22.0	21.0
0.90 x 4				28.0	24.0	22.0

The maximum open area A0 [%] results from the smallest dimensions for pitch and feed and depends on the material.